

Client:**NORDTEK IMEXCO Co Ltd.****Szőnyi út 21/A****1142 Budapest****HUNGARY****QUALITY CERTIFICATE OF DELIVERY**

PARAMETER	METHOD / DEVICE
WEIGHT	Digital scale Axis (precision 0,01g)
HEIGHT	Gawis-OD Agr / Electronic altimeter (precision 0,01mm)
TOP LOAD	Top Load Agr / Niutonomierz cyfrowy BFG N (0,1-500N)
DIAMETER	Gawis-OD Agr / Micrometer of 0,001mm precision, according to DIN 863
COMPONENTS	Gawis-OD Agr / Digital caliper of 0,01mm precision, according to DIN 862
MATERIAL DISTRIBUTION	Gawis-OD Agr / PTG5004 AGR
TOTAL CAPACITY AND FILLING HEIGHT	Combi Agr
HORIZONTAL AND VERTICAL ALIGNMENT	Gawis-OD Agr / Angle gauge, according to DIN 875/0 + Gap gauge (0,05-1,0mm) (max. 1,0mm/100mm)
STABILITY ON THE SURFACE	Flat marble slab + Gap gauge (0,05-1,0mm)
COLOUR	Spectrophotometer Ci5 (laser measurement) according to standard
TIGHTNESS	Vacuum chamber (underpressure of 600mbar during 180s.)
DROP TEST	Trap on 1,5m height

PRODUCT IMPLEMENTATIONS AND QUALITY ANALYSIS ARE PERFORMED WITH THE USE OF THE FOLLOWING DEVICES: Agr Gawis-OD, Top Load/Combi, PTG5004

Shipment/delivery date**2020-09-01**

PRODUCT	BATCH NO.	MATERIAL	COLOUR	PALETTE ID	QUANTITY
104810 (ZZ-FT-AN002-0020-A-K0012-0000)	ZWM-21/09/2020/ UE	PP	Czarny	K000152793, K000152794, K000152795, K000152796, K000152797, K000152798	27 000
105803 (BU-0649-0230-0024-A-00000-0-M-H)	ZWM-21/09/2020/ UE	Polyethylene terephthalate Regranulate	Transparent	P000378611, P000378612, P000378613, P000378614, P000378615, P000378616, P000378617, P000378618, P000378619, P000378620, P000378621, P000378622, P000378623, P000378624, P000378625, P000378626, P000378631, P000378632, P000378633, P000378634, P000378636, P000378649, P000386063, P000386064, P000386065, P000386066, P000386067, P000386068, P000386069, P000386070, P000386071, P000386072, P000386073, P000386074, P000386075, P000386076, P000386077, P000386078, P000386079, P000386080, P000386081, P000386082, P000386083, P000386084, P000386085, P000386086, P000386087, P000386088, P000386089, P000386090, P000386091, P000386092, P000386093, P000386094, P000386095, P000386096, P000386097, P000386098, P000386099, P000386100, P000386101, P000386102, P000386103, P000386104, P000386105	152 100
105932 (BU-0960-0210-0028-A-0003H-0-M-A)	ZWM-21/09/2020/ UE	Polyethylene terephthalate	Brown transparent	P000387636	2 002

PACKAGING FEATURES**Microbiological purity**

In case of the risk occurrence, own tests are recommended.

Stability

Packaging is stable in the temperature range from -10°C to 40°C.

Possible interactions

No data. In case of the risk occurrence, own tests are recommended.

REQUIREMENTS FOR STORAGE AND TRANSPORTATION

Storage areas should be dry, airy, with eliminated sunlight, at the temperature of -10°C to 40°C for bottles and 5-35°C for caps and humidity of 0-90% for bottles and 30-85% for caps.

It is forbidden to store bottles in the open air or expose them to direct sunlight.

Product loading takes place directly before departure. Before pallet loading, the warehouse worker inspects the cleanliness of the trailer and checks if the pallet is not damaged.

All products are subjected to inspection and released into the main warehouse after verification of the Quality Control Department, according to the Product Specification, which is drawn up on the basis of technical drawing, with the use of the above methods and written down in the Measurement Card.