

City Plastics Pty Ltd 61 East Street Brompton 5007 South Australia Ph: (+61) 8, 8346 6500 Fax: (+61) 8, 8346 6711 Email:info@cityplastics.com

Email:info@cityplastics.com.au www.cityplastics.com.au ABN 20 101 181 793 ACN 101 181 793

- Sheet Plastics
- Cut to size & shape
- CNC Router cutting
- Fabrication
- Vacuum Forming
- Boat Screens & windows
- Signs & Displays
- Engineering Plastics
- Ecoscreen Plastic Lattice
- C/S Acrovyn
- Bld/Lic RL155051

MATERIAL SAFETY DATA SHEET, PET

Section 1 | Product and Company Identification

City Plastics Pty Ltd 61 East Street BROMPTON 5007 South Australia

Phone: +61,8,8346 6500 Fax: +61,8,8346 6711 Material Identification Product Name: PET

Chemical Name: POLYETHYLENE TEREPHTHALATE (PET)

CAS Number: 25038-59-9

Product Use: Thermoplastic for fabrication.

Section 2 | Composition/Information on Ingredients

Composition is not hazardous.

Section 3 | Hazards Identification

Ingestion: Not a probable route of exposure. **Skin:** Molten material will cause thermal burns.

Eye: Mechanical irritation only.

Inhalation: Stock shapes are not respirable, avoid breathing dust, as fine particles can be

inhaled and retained in the lungs.

Section 4 First Aid Measures

If exposed to fumes from overheating, move to fresh air. Consult a physician if symptoms persist.

Wash skin with soap and plenty of water.

Flush eyes with water. Consult a physician if symptoms persist.

If molten material contacts skin, cool rapidly with cold water. Do not attempt to peel material from skin. Obtain medical attention to thermal burn.

Chronic effects: None known.

Medical conditions generally aggravated by this material: None known.



City Plastics Pty Ltd 61 East Street Brompton 5007 South Australia

Ph: (+61) 8, 8346 6500 Fax: (+61) 8, 8346 6711

MATERIAL SAFETY DATA SHEET, PET

Section 5 | Fire Fighting Measures

Flash ignition temperature: 350°C / 662°F

Method: ASTM D-1929

Unusual fire, explosion hazards: None known.

Hazardous combustion products: At temperatures above 350°C / 662°F, heavy fuming,

carbon dioxide and carbon monoxide will occur.

Special fire fighting instructions: Fire fighters and others exposed to products of combustion should wear full protective clothing including self-contained breathing apparatus. Fire fighting equipment should be thoroughly decontaminated after use.

Extinguishing media: Water spray or any class a extinguishing agent.

Section 6 | Accidental Release Measures

Spill or release: Clean up by vacuuming or sweeping to prevent falls.

Section 7 | **Handling and Storage**

Practice reasonable care and caution in handling.

Section 8 | Exposure Controls/Personal Protection

Eye: Safety glasses are recommended to prevent particulate matter from entering eyes while grinding or machining.

Skin: Protective gloves are required when handling hot polymer. Also, long sleeve cotton shirt and long pants if handling molten polymer.

Ventilation: Local exhaust at processing equipment to assure that particulate levels are kept at recommended levels.

Respirator: None under normal processing, if ventilation is adequate.

Section 9 | Physical and Chemical Properties

Appearance: Stock shape may be rod, plate or tube form.

Odour: Essentially odourless.

Melting point: 225-260°C / 437-500°F


Solubility in water: Insoluble Volatile content %: <1% Specific gravity: 1.33-1.43

Section 10 | Stability and Reactivity

Stability at room temperature: Stable

Materials to avoid: Strong oxidants and bases.

Conditions to avoid: None known.



City Plastics Pty Ltd 61 East Street Brompton 5007 South Australia

Ph: (+61) 8, 8346 6500 Fax: (+61) 8, 8346 6711

MATERIAL SAFETY DATA SHEET, PET

Section 11 | Toxicological Information

Chronic toxicity: PET does not appear to possess any toxicological properties.

Medical conditions prone to aggravation by exposure: None known.

Carcinogenicity: None known.

Section 12 | Ecological Information

Aquatic toxicity: Toxicity is expected to be low based on insolubility of polymer in water.

Section 13 | Disposal Considerations

Spill or release: Clean up by vacuuming or wet sweeping to minimize dust exposure. **Waste disposal:** Landfill or incineration in compliance with federal, state, and local

regulations.

Section 14 | Transport Information

Hazard class: NA Shipping name: NA

Section 15 | Regulatory Information

NA

Section 16 Other Information

Prepared by: Steven Cook Issued: 1 September 2009

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of City Plastics Pty Ltd, accurate and reliable. Such information is offered solely for your consideration, investigation and verification, and it is not suggested or guaranteed that the hazard precautions or procedures mentioned are the only ones, which exist. City Plastics Pty Ltd makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.