

BASE PAPER

Grease Resistance	Optical Brightening Agent Free	Moisture Impermeability	Application Adjustment	Food Wrapping	Recyclable	
19 19	•	P. OP	149 Ag	40.	•	

The standard base paper with wide usability for further processing.

Base paper is an excellent material for PE/wax lamination with aluminium foil or PE extrusion coating.

CHARACTERISTICS

- White, woodfree, machine finished base paper
- Excellent workability
- Any synthetic and starch adhesives can be used when gluing
- Printable using all common printing techniques
- Paper is available in reels or sheets

TYPICAL VALUES

	Substance	gsm	30	40	50	60	70
	Breaking Length MD	km	9,0	9,0	9,0	9,0	9,0
	Bursting Strength	kPa	120	180	220	260	300
	Brightness (ISO R ₄₅₇₊)	%	Par.	All and	84		100
	Water absorbency (Cobb ₆₀)	gsm	.0.		30		



QUALITY AND ENVIRONMENT





- Recyclable and biodegradable
- Health compliant, suitable for primary food packaging
- Technical data above may be adjusted according to specific application or client's specification

Printing up to 8 colours on our flexographic printer can be provided.

Proper paper storage is a place with a temperature of c. + 20 °C and a relative humidity of 40 to 60 %.



Product is available with FSC® certificate.

The mark of responsible forestry. Forest Stewardship Council [®] (FSC) is an international organization with a respected system and a recognized product label to promote responsible management by the world 's forests.





tel: +420 499 990 222

e-mail: paper@krpa.cz

web: www.krpa-paper.cz