

# Material Safety Data Sheet(MSDS)

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PP(Polypropylene)  
Other Name: -  
Recommended use : May be used to produce molded or extruded particles or as a component of other industrial products.  
Manufacturer or supplier: Shanghai SECCO Petrochemical Company Limited  
4/30F,A Building, Far East International Plaza  
No.319, Xian Xia Road,Shanghai 200051 P.R. China  
Emergency phone/fax : +86-21-52574688

## 2. HAZARDS IDENTIFICATION

NFPA RATINGS (SCALE 0-4) : HEALTH=1 FIRE=1 REACTIVITY=0  
EC CLASSIFICATION (CALCULATED) : No classification assigned.

### EMERGENCY OVERVIEWS :

Solid pellets with slight or no odor. Spilled pellets create slipping hazard.  
Can burn in a fire creating dense toxic smoke. Molten plastic can cause severe thermal burns.  
Fumes produced during melt processing may cause eye, skin and respiratory tract irritation.  
Secondary operations, such as grinding, sanding or sawing, can produce dust which may present an explosion or respiratory hazard.

### POTENTIAL HEALTH EFFECTS :

**EYE** : Product may cause irritation or injury due to mechanical action.

**SKIN** : Pellets not likely to cause skin irritation.

**INGESTION** : Not acutely toxic.

**INHALATION** : Pellet inhalation unlikely due to physical form.

### CHRONIC / CARCINOGENICITY :

**NTP** : Not Tested

**OSHA** : Not Regulated

**IARC** : Not Listed

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

| <u>Chemical Name</u>     | Cont nt (%) | <u>CAS Number</u> | Exposure Limits In Air             |                   |      |
|--------------------------|-------------|-------------------|------------------------------------|-------------------|------|
|                          |             |                   | ACGIH<br>TLV-TWA                   | ACGIH<br>TLV-STEL | IDLH |
| Polyolefin               | 99.25wt%    | 9010-79-1         | 10mg/m3<br>(inhalable<br>fraction) | NA                | NA   |
| Proprietary<br>additives | ≤0.75wt%    | mixture           | -                                  | -                 | -    |

## 4. FIRST AID MEASURES

### MEDICAL RESTRICTIONS :

**EYE :** Remove contact lenses at once. Immediately flush eyes well with copious quantities of water or normal saline for at least 15-20 minutes. If irritation persists, seek medical attention.

**SKIN :** seek medical attention if rash or burn occurs.

**INGESTION :** Not probable. If a large amount is swallowed, seek medical attention.

**INHALATION :** Not Likely to be inhaled due to physical form.

### MELT PROCESSING :

For molten plastic skin contact, cool rapidly flush with water and immediately seek medical attention.

Do not attempt removal of plastic without medical assistance. Do not use solvent for removal.

For processing fume inhalation irritation, leave contaminated area and breathe fresh air. If coughing, difficult breathing or any other symptoms develop seek medical attention at once, even if symptoms develop at a later time.

For skin contact with fume condensate, immediately wash thoroughly with soap and water. If irritation develops seek medical attention.

## 5. FIRE FIGHTING MEASURES

### FIRE FIGHTING :

Approved pressure demand breathing apparatus and protective clothing should be used for all fires. Water spray is the preferred extinguishing medium. This product will melt but will not be carried on the surface for water.

### EXTINGUISHING MEDIA :

Water spray and foam, Water is the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition.

### HAZARDOUS COMBUSTION PRODUCTS :

Hazardous combustion products may include intense heat, dense black smoke, carbon monoxide, carbon dioxide, oxides of phosphorus, hydrogen cyanide, hydrocarbon fragments, hydrogen fluoride, carbonyl fluoride and fluorocarbon fragments.

**FLASH POINT:** Not Applicable

**LOWER FLAMMABLE LIMIT :** Not Established

**UPPER FLAMMABLE LIMIT :** Not Established

**AUTOIGNITION :** Not Established

**FLAMMABILITY CONDITIONS :** Requires a continuous flame source to ignite and sustain combustion.

**EXPLOSION DATA :** Not Established

**IMPACT SENSITIVITY :** Not sensitive to mechanical impact.

**STATIC DISCHARGE :** Not sensitive to static discharge. (See Section 7)

## 6. ACCIDENTAL RELEASE MEASURES

GENERAL :Sweep or gather up material and place in preper container for disposal or recovery. (See Section 13)

## 7. HANDLING AND STORAGE

### HANDLING :

Follow recommendations on label and in processing guide. Prevent contact with skin and eyes. Use good industrial hygiene proctices. Provide adequnte ventilation. Secondary operations such as grinding, sanding or sawing may produce a dust explosion hazard. Use aggressive housekeeping activities to prevent dust accumulation; employ bonding, grounding, venting and explosion relief provisions in accordance with accepted engineering practices.

### STORAGE :

Store in a dry place away from moisture, excessive heat and sources of ignition.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### ENGINEERING CONTROLS :

A continuous supply of fresh air to the workplace together with removal of processing fumes through exhaust systems is recommended. Processing fume condensate may be a fire hazard and toxic;remove periodically from exhaust hoods, duct work amd othwr suricaces using appropriate personal protection. For piwders and residual dusts refer to Section 7.

### PERSONAL PROTECTION :

**EYE/FACE** : Wear safety glasses with side shields or chemical goggles. In addition, use full face shield when cleanning processing fume condensates from hoods,ducts and other surfaces.

**RESPIRATORY** : When handling fumes are not adequstely controlled, use respirator approved for protection from organic vapors and acid gases. When dust or powder from secondary operations, such as grinding, sanding or sawing, are not adequately controlled use respirator approved for protection from dust.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE** : Solid

**COLOR AND APPEARANCE** : Plastic pellet with slight odor

**BOILING POINT** : Not Applicable

**MELTING POINT (°C)** : 160 170

**VAPOR PRESSURE (mmHg)** : Negligible

**VAPOR DENSITY (Air=1)** : Not Applicable

**SPECIFIC GRAVITY** : 1.40 1.60

**WATER SOLUBILITY** : Insoluble

**SOLVENT SOLUBILITY** : Slightly soluble in strong polar slovent or chlorinated solvents

**% VOLATITLES** :Negligible

**pH** :Not Applicable

**ODOR THRESHOLD** :Not Established

**EVAPORATION RATE** :Negligible

**EVAPORATION RATE** :Negligible

**COEFFICIENT WATER / OIL DISTRIBUTION** : Not Established

**COMMENT:** This product does not exhibit a sharp melting point, but softens gradually over a wide temperature range.

## **10. STABILITY AND REACTIVITY**

**STABILITY** : Stable under recommended conditions of Section 7

**REACTIVITY** : Not reactive under recommended conditions of handling, storage, processing and use.

### **CONDITIONS TO AVOID :**

Do not exceed melt temperature recommendations in product literature.

In order to avoid autolgnition/hazardous decomposition of hot thick meases of plastic, purgings should be collected in small, flat shapes or thin strands to allow for rapid cooling and quenching in water.

Do not allow product to remain in barrel at elevated temperatures for extended periods of time ; purge with a general purpose resin. (See Section 8 for respiratory protection advice)

### **HAZARDOUS DECOMPOSITION :**

Major decomposition gases are oxidized hydrocarbons (probably carbon monoxide) and steam. Minor components in decomposition gas may be aldehyde, phenolic compounds, etc.

## **11. TOXICOLOGICAL INFORMATION**

Not Available

## **12. ECOLOGICAL INFORMATION**

Not expected to present any significant ecological problems

## **13. DISPOSAL CONSIDERATIONS**

### **RCRA HAZARDOUS WASTE :**

Products is not a RCRA hazardous waste.

### **WASTE DISPOSAL :**

Recycling is encouraged. Landfill or incinerate in accourdance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine waste classification.

## **14. TRANSPORT INFORMATION**

**DOT HAZARD CLASS:** Not Regulated

**PROPER SHIPPING NAME:** Not Regulated

**IDENTIFICATION NUMBER:** Not Listed

**TDGA:** Not Listed

## 15. REGULATORY INFORMATION

Listed below are chemical substances subject to supplier notification requirements.

### U.S. REGULATIONS :

**TSCA INVENTORY STATUS :** This product complies with the Chemical Substance Inventory requirements of the US EPA TSCA.

**CERCLA SECTION 103 (40CFR302 :** Not Listed

**SARA SECTION 313 (40CFR372.65:** Not Listed

SARA HAZARD CATEGORIES, SARA SECTIONS 311/312 (40CFR370.21)

**ACUTE:** Not Listed

**CHRONIC:** Not Listed

**FIRE:** Not Listed

**REACTIVE:** Not Listed

**SUDDEN RELEASE :** Not Listed

### STATE REGULATIONS :

**California Proposition 65 :** Not Listed

### EUROPEAN REGULATIONS :

**EC NUMBER:** Not assigned

## 16. OTHER INFORMATION

None



# MSDS OF ALUMINUM INGOT

## Section 1: Identification

**Product Name:** Aluminum ingot

**HS Code:** 76011090

**Model:** No data.

**Trademark:** No information.

**Manufacturer/Supplier name:** Hangzhou Rainbow Packaging Co., Ltd

**Address:** No. 242, Huanhu North Road, Qian-Dao-Hu Town, Chun-An, Zhejiang, China

**Postal Code:** 311700

**Tel:** +86-571-64818302

**Fax:** +86-571-64827114

**Email:** ruibo@ruipack.com.cn

**Emergency Phone number:** +86-18868123926

## Section 2: Hazard identification

**Classification of substances or mixtures:** GHS classification according to the series of specifications for classification and labeling of chemicals (GB30000.2-29), this product is not a hazardous substance or mixture. No significant harm to health or environment under normal use.

**Hazard pictogram:** None.

**Signal word:** None.

**Hazard Description:** None.

**Precautionary statement:** None.

**Other hazards:** Do not mix with water. The fire produces toxic smoke.

## Section 3: Composition / information on ingredients

| Chemical name | CAS No.   | Composition(%) |
|---------------|-----------|----------------|
| Aluminum      | 7429-90-5 | 100            |

## Section 4: First-aid measures

**Skin contact:** Wash skin and hair with running water (soap if possible). If there is irritation, consult a doctor.

**Eye contact:** Do not attempt to remove particles that adhere to or are embedded in the eyes. Immediately seek emergency medical assistance or send to hospital for treatment.

**Inhalation:** If smoke, aerosol or combustion products are inhaled, transfer the patient out of the contaminated area.

**Ingestion:** Generally not applicable.

## Section 5: Fire-fighting measures

**Suitable extinguishing medium:** Sand and inert dry powder fire extinguishers shall be used to extinguish fires caused by metal dust. Do not use water, carbon dioxide (CO<sub>2</sub>) or foam fire extinguishers to extinguish the fire.

**Specific hazards:** Although metal powder is generally considered to be nonflammable, it can burn when the powder is very fine and provides high energy. Explosive reaction may occur in contact with water. It can be ignited by friction, heat, sparks or open flame. Metal dust fire moves slowly, but the fire is strong and difficult to put out. It will burn under strong heat, and the burning dust shall not be disturbed. If the dust is stirred to form a cloud, it may cause an explosion. Avoid oxygen (gas) channeling to the large hot metal surface. When heated (heated), the container may explode. Dust and smoke can form explosive mixtures with air. After the fire is extinguished, it may rekindle. The gas produced in the fire may be toxic, corrosive or irritating. Do not use water or foam to extinguish the fire, as explosive hydrogen may be generated.

**Special protection for firefighters:** Wear self-contained positive breathing apparatus and full protective tools.

## Section 6: Accidental release measures

**Personal protective measures, protective equipment and emergency measures:** Avoid inhaling dust and contact with skin and eyes. Wear protective clothing, gloves, safety goggles and dust mask.

**Environmental precautions:** Stop leakage when it is safe. Do not allow the product to enter the sewer.

**Methods and materials for containment and cleaning up:** Immediately remove all spills. Ensure the loading safety under the safety permission. Bundle / collect recyclable products. Place the remaining material in a covered container for disposal.

## Section 7: Handling and storage

**Safe operation:** Provide appropriate exhaust equipment where dust is generated.

**Safe storage:** Store in a cool place. Keep the container closed and store in a dry and ventilated place.

## Section 8: Exposure controls/personal protection

**Occupational exposure limit:**

| Source                                                                      | Component | Substance name | TWA                | STEL    | Peak value |
|-----------------------------------------------------------------------------|-----------|----------------|--------------------|---------|------------|
| Occupational exposure limit for hazardous factors in the workplace in China | Aluminum  | Aluminum dust  | 4mg/m <sup>3</sup> | No info | No info    |

**Engineering control:** When solid substances are handled in powder or crystal form, local ventilation system is required. The ventilation system shall be designed to prevent particles from accumulating or circulating in the workplace.

**Personal protective measures**

**Respiratory protection:** Respiratory protection is not required. To protect against dust damage, use a N95 (US) or P1 (EN 143) dust mask. Respirators use respirators and parts that have been tested and passed government standards.

**Eye protection:** No eye protection is required. Wear chemical safety glasses when dust is present.

**Skin and body protection:** Ordinary work clothes.

**Hand protection:** Wear appropriate protective gloves.

**Other protection:** Operate in accordance with good industrial hygiene and safety practices. Wash hands before rest and at the end of work.

**Section 9: Physical and chemical properties**

**Appearance:** Silver ingot solid.

**Odor:** Odourless.

**Odor threshold:** No data.

**PH:** Not applicable.

**Melting point:** 660.37 °C.

**Specific gravity:** 2.71.

**Boiling point:** 2460 °C.

**Flash point:** Not applicable.

**Evaporation rate:** Not applicable.

**Flammability:** No data available.

**Upper and lower flammability limit or explosion limit:** Not applicable.

**Vapor pressure:** Not applicable.

**Vapor density:** Not applicable.

**Relative density:** No data available.

**Solubility:** No data available.

**Octanol / water partition coefficient:** No data available.

**Spontaneous combustion temperature:** No data available.

**Decomposition temperature:** No data available.

**Viscosity:** No data available.

#### Section 10: Stability and reactivity

**Stability:** Stable under the recommended storage conditions.

**Reactivity:** Hazardous polymerization will not occur.

**Taboos:** Strong acid, strong oxidant, halogen/ halogenating agent.

**Conditions to avoid contact:** High temperature, heat source and ignition source.

**Decomposition products:** No harmful decomposition products will be produced under normal conditions. Combustion is the production of metal oxides, etc.

#### Section 11: Toxicological information

**Acute toxicity:** LD<sub>50</sub> >2000 mg/kg Rat Oral

**Inhalation:** Mechanical treatment of massive metal (such as cutting and grinding) may cause upper respiratory tract irritation.

**Ingestion:** Massive metals and their alloys are "locked" into the metal lattice; Therefore, it is not easy to be bioavailable after ingestion.

**Skin:** Unhealed wounds, abraded or irritated skin should not be exposed to this substance.

**Eyes:** Metal dust in contact with eyes may cause mechanical abrasion or scratch of cornea - these damages are often minor. However, foreign bodies entering the eyeball can cause infection or permanent visual impairment.

**Chronic toxicity or long-term toxic effect:** Metal dust produced by various industrial processes will have a variety of potential hazards to health. Large particles larger than 5 microns will stimulate the nasal cavity and throat, while smaller particles can reduce lung function. Particles smaller than 1.5 microns can be encapsulated in the lung and cause further serious adverse effects on health according to the characteristics of the particles.

**Other information:** No data.

#### Section 12: Ecological information

**Ecological Toxicity:** No data available.

**Biodegradability:** No data available.

**Bioaccumulative potential:** No data available.

**Mobility in soil:** No data available.

**Other harmful effects:** No data available.

#### Section 13: Disposal considerations

**Disposal method:** First, recycle or recycle as much as possible, and then dispose according to relevant national and local regulations.

**Waste precautions:** The facilities and places for waste treatment must comply with the national occupational safety, health and environmental protection standards.

#### Section 14: Transportation information

**UN No.:** Goods not classified as dangerous goods.

ADR, IMDG, IATA

**UN special transport Name:** Goods that are not dangerous goods.

ADR, IMDG, IATA

**Transportation hazard level:** Goods that are not dangerous goods.

ADR, IMDG, IATA

**Packing grade:** Goods that are not dangerous goods.

ADR, IMDG, IATA

**Hazardous environment:** None.

**Special precautions for users:** None.

#### Section 15: Regulatory information

This safety technical instruction complies with the requirements of GB/T 17519-2013. GHS classification is determined according to the series of specifications for classification and labelling of chemicals (GB30000.2-29).

There is no information on the specific safety, health and environmental regulations / rules for this substance or mixture.

**Chemical safety assessment:** No chemical safety assessment has been conducted for this product.

#### Section 16: Other information

**Issue Time:**2022-05-22

**Issue department:** Technical department

**Other information:**

This MSDS is prepared based on the information we can collect. However, the data and the assessment of hazards and toxicity are not guaranteed. Before use, please investigate the hazard and toxicity information, and give priority to the laws and regulations of the organization, region and country using the product.

In consideration of safety, the product should be used immediately after purchase. Some new information or amendments will be added later. If the product is used far beyond the warranty period or you have any questions, please contact us. The warnings stated apply only to normal use. In case of special use, sufficient care must be taken in addition to ordinary safety measures.

It should be noted that all chemicals have "unknown hazards and toxicity", which will vary greatly under different use and storage conditions. The product shall be used by experienced operators with professional knowledge or under the guidance of experts during the whole process from opening to storage to abandonment. Safe use conditions must be established based on the personal responsibility of each user.

# TECHNICAL INFORMATION SHEET

COMPANY: Nordtek Imexco Kft

DATE: 2024-02-25

|                       |                                                                                                                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description   | Perfume glass bottle, transparent, 5 ml                                                                                                                                                                                                         |
| Product Reference No. | 108309                                                                                                                                                                                                                                          |
| Features              | <ul style="list-style-type: none"><li>• non-toxic,</li><li>• Flame Retardant</li><li>• Good Stiffness</li><li>• Good Strength</li><li>• Halogen Free</li><li>• High Impact Resistance</li><li>• It is suitable for cosmetic packaging</li></ul> |
| Uses                  | <ul style="list-style-type: none"><li>• Consumer Applications</li><li>• Electrical/ Electronic applications</li><li>• Cosmetic applications</li><li>• General Purpose</li><li>• Industrial Applications</li></ul>                               |

## COMPOSITION/ INFORMATION ON INGREDIENTS:

| Trade name | % in product | Chemical names/INCI name | CAS       | % active in raw material |
|------------|--------------|--------------------------|-----------|--------------------------|
| SiO2       | 72±4%        |                          | 9003-07-0 | 72%                      |
| Al2O3      | 2±2%         |                          |           | 2%                       |
| CaO        | 9±3%         |                          |           | 9%                       |
| MgO        | 2±2%         |                          |           | 2.5%                     |
| K2O+Na2O   | 14±3%        |                          |           | 14.8%                    |
| Fe2O3      | 0.3±0.25%    |                          |           | 0.4%                     |

## TECHNICAL PROPERTIES:

| Index                                  | Value             |
|----------------------------------------|-------------------|
| Appearance                             | Amber /Clear      |
| The relative density (water=1 kg/dm3 ) | 0.89~0.91 k g/dm3 |
| Melting point(℃)                       | 150~170           |
| Decomposition temperature (℃)          | 350               |
| Heat distortion temperature (℃)        | 100               |
| Vicat softening temperature            | 150               |
| MFR                                    | 1~40              |
| Contractibility rate                   | 1.8~2.5%          |