

DECLARATION OF CONFORMITY

We hereby certify that the following product complies with all applicable rules, bans, regulations and standards below.


Item: **108329 - Lid for jar, 70/400, screw on, black, ribbed, aluminum, matte**

Regulation(EU) **No 10/2011**, Standard for EU Food Contact Compliance

Regulation(EC) **No 1999/45**, Standard for Classification



Regulation(EC) **No 2009/48**, Standard for heavy metal content

Budapest, 2026.02.25


NORDTEK IMEXCO KFT
1142 SZŐNYI ÚT, BUDAPEST, HUNGARY
TEL: +36-1-363-1447; FAX: +36-1-363-1448
VAT NO: HU12244692
IBAN: HUN4 1083 0007 5400 4028 0000 0000 0000 0000

SPECIFICATION P593

PARAMETER	METHOD / DEVICE
WEIGHT	Digital scale Axis (d=0.01)
HEIGHT	Gawis-OD Agr / Digital altimeter Mitutoyo (0.01mm/0,0005)
TOP LOAD	Top Load Agr / Digital Newton meter BFG N (0,1-500N)
DIAMETER	Gawis-OD Agr / Micrometer of 0.01mm precision, according to DIN 863
COMPONENTS	Gawis-OD Agr / Digital caliper of 0.001mm precision, according to DIN 862
WALL THICKNESS	Gawis-OD Agr / Wall thickness gauge - PG9800T Scanner
MATERIAL DISTRIBUTION	Gawis-OD Agr / PG9800T Agr
TOTAL CAPACITY AND FILLING HEIGHT	Combi Agr
HORIZONTAL AND VERTICAL ALIGNMENT	Gawis-OD Agr / Angle gauge, according to DIN 875/0 + Gap gauge (0.05-1,0mm) (max. 1.0mm/100mm)
STABILITY ON THE SURFACE	Flat marble slab + Gap gauge (0.05-1.0mm)
COLOUR	Spectrophotometer SP62 (laser measurement) according to standard
DROP TEST	Trap on 1.5m height
TIGHTNESS	Vacuum chamber (underpressure of 600 mbar during 180 s)
PRODUCT IMPLEMENTATIONS AND QUALITY ANALYSIS ARE PERFORMED WITH THE USE OF THE FOLLOWING DEVICES: Agr Gawis-OD, Top Load/Combi, PTG5004, PG9800T	



Capacity:	100,0ml
Thread:	STC70/400
Material:	polyethylene terephthalate

Parameters	Given dimensions	Tolerance
Height (mm)	39,00	+/- 1,0
Base diameter (mm)	72,00	+/- 1,0
Weight (g)	15,00	+/- 1,0
Total capacity (ml)	136,00	+/- 4,0
Distance to the cap (mm)	10,50	+/- 0,5
Outer diameter thread with a roll (mm)	69,06	+/- 0,2
Inner diameter of the hole (mm)	64,10	+/- 0,2
VERTICAL (max 1/100mm)	V	V
IT SHRINKS ON SURFACE SECONDARY	X	-
SHAPE CONFORMITY	V	-
STABILITY BASE BOTTLE	V	-

PACKAGING	
ON PALLET	4940
LAYERS	13
ON LAYER	2x190
PALLET HEIGHT	1240,00mm

06.11.2014

date, authorised person signature

We have implemented and certified Management System PN EN ISO 9001:2008, ISO 15378:2011, ISO 15593:2010